

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

Issue date: 12/18/2025 Revision date: 01/22/2026 Supersedes version of: 12/18/2025 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : IKAROS MOB Light & Smoke Signal MKIV
Product code : 345105

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use, consumer use
Use of the substance/mixture : Man over board signal

1.3. Details of the supplier of the safety data sheet

Hansson PyroTech AB
Köpingsvägen 35
SE-711 31 Lindesberg
Sweden
Phone +46 58187250
E-mail info@hansson-pyrotech.com
Website www.hansson-pyrotech.com

1.4. Emergency telephone number

Organisation	Emergency telephone number	Opening hours
Hansson PyroTech AB, Köpingsvägen 35 SE-711 31 Lindesberg, Sweden	+46 581 87111	24-hour emergency contact

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GHS

Expl. 1.4	H204
Acute Tox. 4 (oral)	H302
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H335
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Adverse physicochemical, human health and environmental effects

Fire or projection hazard.

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

2.2. Label elements

Labelling according to GHS

Hazard pictograms



GHS01

Signal word

: Warning

Contains

: 1,4-dihydroxy-9,10-anthraquinone, potassium chlorate

Hazard statements

: H204 - Fire or projection hazard.

Precautionary statements

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P234 - Keep only in original container.

P240 - Ground/bond container and receiving equipment.

P250 - Do not subject to grinding/shock/friction.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P370+P372+P380+P373 - In case of fire: Explosion risk. Evacuate area. DO NOT fight fire when fire reaches explosives.

P370+P380+P375 - In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

P401 - Store in accordance with local regulations on explosives.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional and national regulations.

2.3. Other hazards

The mixture does not contain substance(s) having endocrine disrupting properties to human or to the environment in concentrations equal to or greater than 0,1 %.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to GHS
1,4-dihydroxy-9,10-anthraquinone	CAS-No.: 81-64-1	37,6	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Acute 1; H400; M-factor M=10 Aquatic Chronic 1; H410; M-factor M=10
potassium chlorate	CAS-No.: 3811-04-9	26,5	Ox. Sol. 1, H271 Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight)

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: If you feel unwell, seek medical advice.

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Unlikely due to the state of the chemical.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: The chemical may irritate skin and cause itching, burning and redness. Allergic reaction symptoms can be: redness, swelling, itching, blistering.
Symptoms/effects after eye contact	: May cause irritation of the eyes, and cause redness and watering.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use foam, dry chemical, CO2 or mist early in the fire.
Unsuitable extinguishing media	: Once the product is lit up, it is very difficult to extinguish with any extinguishing media.

5.2. Special hazards arising from the substance or mixture

Fire or explosion hazard	: Fire or projection hazard in the event of ignition or initiation.
Hazardous decomposition products in case of fire	: Dense orange smoke that can be ignited in a confined space.

5.3. Advice for firefighters

Firefighting instructions	: Evacuate area. Move containers away from the fire area if this can be done without risk. Remove all sources of ignition. Do not fight fire when fire reaches explosives. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel.

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Using a clean shovel, put the material in a dry container and cover without compressing it.
Methods for cleaning up	: Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store only in the original packaging and according to the local regulations regarding the storage of explosive materials.
--------------------	---

7.3. Specific end use(s)

See section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The product does not contain any substances with occupational exposure limits for respiratory tract exposure.

8.2. Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Eyewash facilities and emergency shower should be available at the workplace.

Personal protective equipment:

The personal protective equipment must follow the OSHA regulations found in 29 CFR 1910.132 and should be selected on advice from the supplier of such equipment. The protective equipment recommended below are only suggestions, and should be selected on advice from the supplier of such equipment. The protection equipment's suitability and durability will depend on application.

Eye protection:

Shatter proof glasses or goggles if there is a risk of eye contact.

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

Eye protection	
Type	Standard
polycarbonate	ANSI/ISEA Z87.1-2020: American National Standard For Occupational And Educational Personal Eye And Face Protection Devices

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection			
Type	Material	Thickness (mm)	Standard
Disposable gloves or reusable gloves	Leather or similar	No data available	ANSI/ISEA 105-2016 American National Standard For Hand Protection Classification

Respiratory protection:

If dust is produced: dust mask with filter type P2

Respiratory protection			
Device	Filter type	Condition	Standard
Mask with particle filter	P2	Dust formation	type N95

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Yellow
Appearance	: Aluminium tube inserted in a floating body made of plastic with an orange ribbon; Orange label; Black igniter
Odour	: None
Odour threshold	: Not applicable
Melting point	: Not available
Freezing point	: Not applicable
Boiling point	: Not applicable
Flammability	: Contents are flammable
Explosive properties	: Fire or projection hazard
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: > 200 °C (392 °F)
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: Not applicable
Solubility	: Insoluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not applicable

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

Relative density : Not available
Relative vapour density : Not available
Particle size : Not available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Risk of explosion in contact with sulfuric acid.

10.4. Conditions to avoid

Avoid temperature above 75 °C (167 °F).

10.5. Incompatible materials

Sulfuric acid.

10.6. Hazardous decomposition products

None under normal conditions. See also section 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GHS

Acute toxicity (oral) : Harmful if swallowed. ATEmixture > 300 ≤ 2000 mg/kg
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

1,4-dihydroxy-9,10-anthraquinone (CAS 81-64-1)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2500 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure : May cause respiratory irritation.

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

IKAROS MOB Light & Smoke Signal MKIV	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) having endocrine disrupting properties to human or to the environment in concentrations equal to or greater than 0,1 %.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.

1,4-dihydroxy-9,10-anthraquinone (CAS 81-64-1)

EC50 - Crustacea [1]	0.134 mg/l Daphnia magna
EC50 72h - Algae [1]	0.00757 mg/l Desmodesmus subspicatus

12.2. Persistence and degradability

1,4-dihydroxy-9,10-anthraquinone (CAS 81-64-1)

Degradability : 52% degraded after 20 days (Closed bottle test)

12.3. Bioaccumulative potential

1,4-dihydroxy-9,10-anthraquinone (CAS 81-64-1)

Persistence	BCF: 30.9 Log Pow: 2.34
-------------	----------------------------

12.4. Mobility in soil

Not expected to be mobile.

12.5. Results of PBT and vPvB assessment

IKAROS MOB Light & Smoke Signal MKIV

Contains no PBT and/or vPvB substances ≥ 0.1% (w/w).

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) having endocrine disrupting properties to human or to the environment in concentrations equal to or greater than 0,1 %.

12.7. Other adverse effects

No additional information available

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to 40 Code of Federal Regulations (CFR) Part 261.

Waste treatment methods : Hazardous waste as regulated under RCRA - Resource Conservation and Recovery Authorization Act Hazardous waste.

Waste fireworks may be RCRA hazardous waste due to their ignitability, toxicity, and/or reactive nature. The owner or operator must take precautions to prevent accidental ignition or reaction of ignitable or reactive waste. This waste must be separated and protected from sources of ignition or reaction including but not limited to: open flames, smoking, cutting and welding, hot surfaces, frictional heat, sparks (static, electrical, or mechanical), spontaneous ignition (e.g., from heat-producing chemical reactions), and radiant heat. While ignitable or reactive waste is being handled, the owner or operator must confine smoking and open flame to specifically designated locations. "No Smoking" signs must be conspicuously placed wherever there is a hazard from ignitable or reactive waste.

Sewage disposal recommendations : Disposal must be done according to official regulations. Do not discharge into drains or rivers.

Additional information : DO NOT TRY TO DISMANTLE THE PRODUCT!

EPA Hazardous Waste Number : D001 (Ignitable)

SECTION 14: Transport information

US Department of Transportation Reference number: EX2005040230

Swedish Civil Contingencies Agency (MSB) Cert No: 2025-05130

Packaging in cardboard may be transported with UN 0197

Hazmat Table (49 CFR 172.101) Road / Rail	IMDG	IATA
UN 0197	UN 0197	UN 0197
SIGNALS, SMOKE	SIGNALS, SMOKE	Signals, smoke
UN 0197 SIGNALS, SMOKE, 1.4G, ENVIRONMENTALLY HAZARDOUS	UN 0197 SIGNALS, SMOKE, 1.4G, MARINE POLLUTANT/ ENVIRONMENTALLY HAZARDOUS	UN 0197 Signals, smoke, 1.4G, ENVIRONMENTALLY HAZARDOUS
1.4G	1.4G	1.4G
 	 	 
Not applicable	Not applicable	Not applicable
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-B EmS-No. (Spillage): S-X	Dangerous for the environment: Yes

Packaging in steel cage and cardboard may be transported with UN 0507

Hazmat Table (49 CFR 172.101) Road / Rail	IMDG	IATA
UN 0507	UN 0507	UN 0507

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

US FEDERAL

TSCA:

CAS No 81-64-1 9,10-Anthracenedione, 1,4-dihydroxy- is listed on the TSCA inventory list, Active
CAS No 3811-04-9 Chloric acid, potassium salt (1:1) is listed on the TSCA inventory list, Active

NFPA rating

Flammability (NFPA rating; red): 2 (Materials that must be moderately heated before ignition can occur)

Health (NFPA rating; blue): 1 (Materials that cause irritation upon exposure, but only minor injury is sustained even if no medical treatment is provided)

Instability-reactivity (NFPA rating; yellow): 1 (Normally stable, even under fire exposure conditions, and is not reactive with water)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes

Section	Changed item	Comments
	Revision date	Added
1.4	Emergency telephone number	Modified

Abbreviations and acronyms:

ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

Abbreviations and acronyms:	
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Expl. 1.4	Explosives, Division 1.4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Ox. Sol. 1	Oxidising Solids, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H204	Fire or projection hazard.
H271	May cause fire or explosion; strong oxidiser.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

IKAROS MOB Light & Smoke Signal MKIV

Safety Data Sheet

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Expl. 1.4	H204	Tested
Acute Tox. 4	H302	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.